PLANAR When image experience matters.

LUX80 Touch

Specification	Detail
Product Name	LUX80 Touch
Screen Size	80 in. (diagonal)
Orientation	Landscape/Portrait
Recommended Usage	24/7
Aspect Ratio	16:9
Brightness (typ)	700 nits
Backlight	Edge-Lit LED
Contrast Ratio (typ)	5000:1
Response Time (typ)	4 ms
Frame Rate	120Hz
Viewing Angle (typ)	176H,V
Native Resolution	Full HD 1920 x 1080 (1080p)
Display Color	>1 billion colors. Full 10 bit data path
Surface Treatment	Anti-Reflective 3mm - ERO™ Optically Bonded Vandal Glass Protection
Control and Monitoring	RS232/LAN with SNMP
Line Voltage	100-240V; 50/60Hz
Power Consumption (typ)	350W
External Connections	DisplayPort, HDMI, VGA
Operating Temperature	0°F to + 104°F (0°C to + 40°C)
Storage and Transport Temperature	-4°F to + 140°F (-20°C to + 60°C)
Humidity	20 to 90% RH
Cabinet Dimensions (W x H x D)	73.5" x 43.1" x 3.4" (1867.8mm x 1095.8mm x 85.4mm)
Bezel Width	1.9" (48mm)
Weight	243 lbs (110 kg)
Weight (Shipping)	288 lbs (131 kg)
Touch Technology	IR 6 point touch
OS Compatibility	Windows 7, Vista, XP, Mac OSX and Linux
Bezel color	Black or white
Mounting	Planar Profile Mounting System or VESA: 600 x 800 mm; 4 holes
Approvals	FCC Class A, EN60950, CE
Warranty	3 years Advance Exchange

Other Features	Integrated media player storage with AC power, redundant power supply, compatible with Planar Profile mounting system or UltraLux free-standing pedestals
UPC	8 10689 06801 3

For more information, please visit www.planar.com

Specifications are subject to change without notice.
Specification Report Date: 7/15/2013
(c)Copyright 2013 Planar Systems, Inc. All rights reserved